

Flushing Sink



FLF2

Scan QR code
to view our
installation notes



To order this item please advise:

- Overall bench top dimensions
- Bowl size: 400x400, 350mm Dia. or custom
- Waste size: 100mm
- Grade of stainless: 304 or 316
- Splashback size: 100mm or custom
- Mounting type: wall brackets or on joinery

Product Info:

- Hygienically disposes liquid & solid waste
- Concealed internal flushing bowl rim
- Wet-bead edge around bench top surface
- Manufactured to custom sizes
- Suits bench top or wall mounting

Suggested Accessories:



TW-ST5
Slophopper Trigger Spray

FLF 2 CONICAL Bowl Sizes I.D.

Ø300

Ø350

Ø400

Ø450

Ø500

**custom -
consult BRITEX**

INSTALLATION NOTES

1) Water connection for bowl is located below bench top. 2) Water supply to 25mm BSP connection on flushing bowl should be minimum 3/4" and 250kPa (500kPa max) to ensure bowl flushes solid waste adequately. (1/2" for liquid waste only) 3) Where 100mm outlet is requested, a 101mm OD stainless tube dropper waste is supplied for connection to trap as specified by consultant (not supplied). 4) Wall mounting brackets and/or support frame can be supplied where requested. 5) Suggested mounting height is 900mm AFL to front edge of sink.

