# SUPERSTEP URINAL







Image shows Recessed Superstep Urinal.

Floor Mounted Model is supplied with a kick plate.



- · WELS and WaterMark certified
- Extra wide hinged grated step
- Particularly suited to early education facilities
- Compatible with BRITEX sensor flush systems
- Recessed or floor mounted models
- Vandal resistant design
- · Hygienic, no drip step area
- Water saver sparge system
- Manufactured to custom lengths



The BRITEX Superstep Urinal has been developed specifically for use in early education facilities. The extra wide step encourages younger boys to stand on the flushed tray area and prevents splashing or dripping that can cause unhygienic conditions. Full flushing of the tray along with our weir style sparge ensures no build up to cause unpleasant odours. Available in recessed and floor mounted styles. WaterMark and WELS certified as required by plumbing regulations and government legislation.



BRITEX S.S. Recessed/Floor Mounted Superstep Urinal - XXXXmm Long x 900mm Wide. WELS rating and WaterMark Level 1 certified. Complete with BRITEX Smart SaniFlush Sensor System - Product Code USUP

\*RED TEXT may denote a variable where one option only is to be selected, a nominal dimension that needs to be specified, or an optional feature that can be removed if not required. Please refer to the back of this page for additional specification details and options.

**SYDNEY** 

VISIT BRITEX.COM.AU TO DOWNLOAD BIM FILES, CAD DRAWINGS AND THE MOST CURRENT PRODUCT LITERATURE



MELBOURNE Britex Place, Mirra Crt Bundoora VIC 3083 t (03) 9466 9000

16 Northumberland Drv Taren Point NSW 2229 t (02) 9531 2100 e nsw@britex.com.au PERTH
Unit 1/8 Principal Link
Malaga WA 6090
t (08) 9249 5464

H BRISBANE
19 Manilla St
0 East Brisbane QLD 4169
4 t (07) 3363 2400

ADELAIDE
The Britex Group
SA State Office
t 1300 764 744
e sa@britex.com.au

# SUPERSTEP URINAL

PRODUCT CODE



## **HOW TO SPECIFY: Superstep Urinal**

Sample Specification Code

A B C D E F

= Superstep Urinal, 1800mm Long, Recessed, Rear Entry, 100mm Left Hand Waste

#### Specification Key

- A = Product Code
- B = Urinal Length (mm)
- C = Mounting Options
  FM : Floor Mounted
- D = Entry Point
- T : Top Entry

  R : Rear Entry
- E = Waste Outlet Size
- F = Waste Outlet Position
- L : Left Hand Waste R : Right Hand Waste


# Water Inlets for Urinals:


One water inlet is required for every 1800mm of Urinal, or part thereof.

e.g. 600mm - 1800mm = 1 inlet 1801mm - 3600mm = 2 inlets 3601mm- 5400mm = 3 inlets


### Standard sizes:

1500mm, 1800mm, 2000mm, 2400mm





### MODEL USUP Front Elevation



Recommended floor cut out for recessed model is 940W x 160D x Urinal Length

MODEL USUP Typical Section (Recessed Model)

### MODEL USUP Plan

guide

# When specifying this product please include:



- Product Name and Code
- Product Length
- Top or rear Water Entry
- Size and position of **Outlet**



- Smart SaniFlush Sensor System: pg 3.01Outlet size: 100mm or custom
- Outlet position (left/right end preferred)
- Inlet size 38mm
- Free standing ends (if not between walls)
- Type 316 S.S. (Export models)
- Joining strip for joining modular lengths

VISIT BRITEX.COM.AU TO DOWNLOAD BIM FILES, CAD DRAWINGS AND THE MOST CURRENT PRODUCT LITERATURE.

Last Revised Feb 2024 | 0



