

HAND WASHING TAPWARE

WALL MOUNTED

11.08

TAPWARE

HAND WASHING TAPWARE - WALL MOUNTED




WELS REG # T09780



TW-0030

Cam Action Deluxe Bib Tap

Incorporates vandal resistant, twist action handle for instant shut off to minimise water wastage. Heavy duty, bright CP finish, designed for use in public areas, schools and commercial facilities.




WELS REG # T09793



TW-0008

Vandal Resistant DPW (NSW) Deluxe Bib Tap

NSW DPW approved bib tap with vandal resistant aerator and handle. Includes loose jumper valve and 8L/min flow regulator. Commonly installed on wash troughs in schools and public amenities.



WELS REG # T09781




WELS REG # T09788



TW-0010 (Hot) TW-0011 (Cold)

Vandal Resistant Deluxe Bib Tap

Bib taps with aerator, vandal resistant handles and loose jumper valves. Commonly installed in schools, public amenities and in commercial projects.



Wall Mounted Sensor Taps

The Britex wall mounted sensor unit is a sensor operated hands free unit that is installed to the rear of sinks & basins. It operates by sensing an object, usually a hand, passing within around 7cm of the front of the sensor unit. It uses a beam of invisible Infrared light which, if reflected from an object back to the sensor, will operate the unit. When an object is sensed and removed from the sensor's view, the unit opens the solenoid valve. The valve will remain open & water will flow until an object is again passed in front of the sensor, closing the solenoid valve. The solenoid valve opens when the object leaves the sensor beam. It is not necessary for the object to remain in the beam for the unit to keep the valve open. When shutting the water off, the valve closes as soon as the object enters the beam. If the solenoid valve remains open for more than 45-60 seconds, the unit will time out & close the valve automatically. This is intended to prevent over flows, etc. To turn the tap on again, pass your hand by the sensor unit to open the valve.



WELS REG # T28188

TW-WMS275

Scrub Trough Sensor Tap

Supplied with 275mm long outlet and Britex Wall Mounted Sensor Unit. Scrub Trough Sensor Tap assembly suited specifically to Surgeon's Scrub Troughs.





WELS REG # T28146

TW-WMS165

Wall Mounted Sensor Tap

Supplied with 165mm long outlet and Britex Wall Mounted Sensor Unit.



WELS REG # T30714

TW-WMS225

Wall Mounted Sensor Tap

Supplied with 225mm long outlet and Britex Wall Mounted Sensor Unit.

VISIT BRITEX.COM.AU TO DOWNLOAD BIM FILES, CAD DRAWINGS AND THE MOST CURRENT PRODUCT LITERATURE.

Last Revised 2019



Due to ongoing research and our commitment to product development, details are subject to change without notice. Details accurate at time of print.

Please refer to britex.com.au for the most current product information. Allow +/- 5mm tolerance for dimensions and setouts shown in product literature.

britex.com.au | info@britex.com.au | A.B.N 83 004 309 737



Quality ISO 9001