

Floor Mounted Cleaner's Sink



CSF

Scan QR code
to view our
installation notes



Product Info:

- OH&S friendly design
- S.S. hinged bucket grate
- 35L bowl capacity
- 50mm waste supplied
- Optional splashback extension(s)
- Choose grade 304 or 316 S.S.

Suggested Tapware:

(see Tapware Section: 11 for complete range of options)



TW-SET-01
Wall Sink Set
with Fixed Spout



TW-SET-04
Wall Sink Set
with Upswept
Swivel Spout



TW-SET-05
Wall Sink Set
with Gooseneck
Swivel Spout



TW-0010/TW-0011
Vandal Resistant
Hot and Cold
Deluxe Bib Taps

INSTALLATION NOTES

1) A plumbing waste connection (trap) should be pre-installed in floor recess before connecting sink. **2)** Unit is supplied in two main components: top piece (basin and grate) and bottom piece (shroud). **3)** Affix offset bracket (supplied) to floor in position to secure front edge of shroud. **4)** To install, connect trap to the supplied 50mm waste on basin unit before attaching shroud to basin. **5)** Shroud connects to basin unit via 8 fixing points (screws supplied). **6)** Assembled sink can then be secured to rear wall by drilling fixing holes into blade upstand (if desired) then silicon sealed around perimeter.

